



versaSplit XLR3 DMX/RDM Input module

Category

A) DMX Splitters & Wireless DMX

Description

XLR3 input module for versaSplit



Mechanical

- Material: Metal
- Overall Dimensions: 44 mm (H) x 76 mm (W) x 76 mm (D)
- Mass: 0.12 kg
- Country of Manufacture: United Kingdom

Power & Electrical

- Input Voltage: 3.3V
- Input Power: n/a

Environmental

- Operating Temperature: 0°C to 40°C
- Storage Temperature: -10°C to +50°C
- Operating Relative Humidity (max): 80% Non-Condensing
- IP Rating: IP20 Indoor Use Only
- Certification: CE FCC, WEEE, RoHS
- Warranty: 2 Year (Return to Base)

Configuration / Indication

- Split / Fix switch
- LED indication: Power / Isolation / Data Activity

Control / Data Connections

- Input Protocols: DMX512, DMX512 (1990), DMX512-A, RDM V1.0 (E1.20 - 2006 ESTA Standard)
- Connectors: (1) XLR3 male input; (1) XLR3 female loop-through

DMX512 Input

- Input mode: optically isolated
- Input ESD protection: 12kV
- Input voltage protection: +/- 80V

Package Contents

- versaSplit XLR3 DMX/RDM input module
- Datasheet

Ordering Info

Product Code: vSplit XLR3



www.ArtisticLicence.com

Artistic Licence, The Mould Making Workshop
Soby Mews, Bovey Tracey, TQ13 9JG, UK

Sales@ArtisticLicence.com
Support@ArtisticLicence.com
Tel: +44 (0) 20 8863 4515

Due to our policy of continuing product improvement specifications are subject to change without notice